

Energy-aware Vehicle Routing in Networks with Charging Nodes^{*}

Tao Wang^{*} Christos G. Cassandras^{**} Sepideh Pourazarm^{***}

^{*} *AirCenter Operations Research group, Sabre Airline solutions(e-mail: tao.wang@sabre.com)*

^{**} *Division of Systems Engineering and Center for Information and Systems Engineering, Boston University(e-mail: cgc@bu.edu)*

^{***} *Division of Systems Engineering and Center for Information and Systems Engineering, Boston University(e-mail: sepid@bu.edu)*

Abstract: We study the problem of routing vehicles with energy constraints through a network where there are at least some charging nodes. We seek to minimize the total elapsed time for vehicles to reach their destinations by determining routes and recharging amounts when the vehicles do not have adequate energy for the entire journey. For a single vehicle, we formulate a mixed-integer nonlinear programming (MINLP) problem and derive properties of the optimal solution allowing it to be decomposed into two simpler problems. For a multi-vehicle problem, including traffic congestion effects, we use a similar approach by grouping vehicles into “subflows.” We also provide an alternative flow optimization formulation leading to a computationally simpler problem solution with minimal loss in accuracy.

1. INTRODUCTION

The increasing presence of Battery-Powered Vehicles (BPVs), such as Electric Vehicles (EVs), mobile robots and sensors, has given rise to novel issues in classical network routing problems [Laporte [1992]]. More generally, when the entities in the network are characterized by physical attributes exhibiting a dynamic behavior, this behavior can play an important role in the routing decisions. In the case of BPVs, the physical attribute is *energy*. There are four BPV characteristics which are crucial in routing problems: limited cruising range, long charge times, sparse coverage of charging stations, and the BPV energy recuperation ability [Artmeier et al. [2010]] which can be exploited. In recent years, the vehicle routing literature has been enriched by work aiming to accommodate these BPV characteristics. For example, by incorporating the recuperation ability of EVs (which leads to negative energy consumption on some paths), extensions to general shortest-path algorithms are proposed in Artmeier et al. [2010] that address the energy-optimal routing problem. The energy requirements in this problem are modeled as constraints and the proposed algorithms are evaluated in a prototypical navigation system. Extensions provided in Eisner et al. [2011] employ a generalization of Johnson’s potential shifting technique to make Dijkstra’s algorithm applicable to the negative edge cost shortest-path problem so as to improve the results and allow for route planning of EVs in large networks. This work, however, does not consider the presence of charging stations, modeled as nodes in the network. Charging times are incorporated into a multi-constrained optimal path planning problem

in Siddiqi et al. [2011], which aims to minimize the length of an EV’s route and meet constraints on total traveling time, total time delay due to signals, total recharging time and total recharging cost. A particle swarm optimization algorithm is used to find a suboptimal solution. In this formulation, however, recharging times are simply treated as parameters and not as controllable variables. In Khuller et al. [2011], algorithms for several routing problems are proposed, including a single vehicle routing problem with inhomogeneously priced refueling stations for which a dynamic programming based algorithm is proposed to find a least cost path from source to destination. More recently, an EV Routing Problem with Time Windows and recharging stations (E-VRPTW) was proposed in Schneider et al. [2012], where an EV’s energy constraint is first introduced into vehicle routing problems and recharging times depend on the battery charge of the vehicle upon arrival at the station. Controlling recharging times is circumvented by simply forcing vehicles to be always fully recharged. In the Unmanned Autonomous Vehicle (UAV) literature, Sunder and Rathinam [2012] consider a UAV routing problem with refueling constraints. In this problem, given a set of targets and depots the goal is to find an optimal path such that each target is visited by the UAV at least once while the fuel constraint is never violated. A Mixed-Integer Nonlinear Programming (MINLP) formulation is proposed with a heuristic algorithm to determine feasible solutions.

In this paper, our objective is to investigate a vehicle total traveling time minimization problem (including both the time on paths and at charging stations), where an energy constraint is considered so that the vehicle is not allowed to run out of power before reaching its destination. We view this as a network routing problem where vehicles control not only their routes but also times to recharge at various nodes in the network. Our contributions are twofold. First, for the single energy-aware vehicle routing problem, for-

^{*} The authors’ work is supported in part by NSF under Grant CNS-1139021, by AFOSR under grant FA9550-12-1-0113, by ONR under grant N00014-09-1-1051, and by ARO under Grant W911NF-11-1-0227.

mulated as an MINLP, we show that there are properties of the optimal solution and the energy dynamics allowing us to decompose the original problem into two simpler problems with inhomogeneous prices at charging nodes but homogeneous charging speeds. Thus, we separately determine route selection through a Linear Programming (LP) problem and then recharging amounts through another LP or simple optimal control problem. Since we do not impose full recharging constraints, the solutions obtained are more general than, for example, in Schneider et al. [2012] and recover full recharging when this is optimal. Second, we study a multi-vehicle energy-aware routing problem, where a traffic flow model is used to incorporate congestion effects. This system-wide optimization problem appears to have not yet attracted much attention. By grouping vehicles into “subflows” we are once again able to decompose the problem into route selection and recharging amount determination, although we can no longer reduce the former problem to an LP. Moreover, we provide an alternative flow-based formulation such that each subflow is not required to follow a single end-to-end path, but may be split into an optimally determined set of paths. This formulation reduces the computational complexity of the MINLP problem by orders of magnitude with numerical results showing little or no loss in optimality.

The structure of the paper is as follows. In Section 2, we introduce and address the single-vehicle routing problem and identify properties which lead to its decomposition. In Section 3, the multi-vehicle routing problem is formulated, first as an MINLP and then as an alternative flow optimization problem. Simulation examples are included for the multi-vehicle routing problem illustrating our approach. Finally, conclusions and further research directions are outlined in Section 4.

2. SINGLE VEHICLE ROUTING

We assume that a network is defined as a directed graph $G = (\mathcal{N}, \mathcal{A})$ with $\mathcal{N} = \{1, \dots, n\}$ and $|\mathcal{A}| = m$ (see Fig. 1). Node $i \in \mathcal{N}/\{n\}$ represents a charging station and $(i, j) \in \mathcal{A}$ is an arc connecting node i to j (we assume for simplicity that all nodes have a charging capability, although this is not necessary). We also define $I(i)$ and $O(i)$ to be the set of start nodes (respectively, end nodes) of arcs that are incoming to (respectively, outgoing from) node i , that is, $I(i) = \{j \in \mathcal{N} | (j, i) \in \mathcal{A}\}$ and $O(i) = \{j \in \mathcal{N} | (i, j) \in \mathcal{A}\}$.

We are first interested in a single-origin-single-destination vehicle routing problem. Nodes 1 and n respectively are defined to be the origin and destination. For each arc $(i, j) \in \mathcal{A}$, there are two cost parameters: the required traveling time τ_{ij} and the required energy consumption e_{ij} on this arc. Note that $\tau_{ij} > 0$ (if nodes i and j are not connected, then $\tau_{ij} = \infty$), whereas e_{ij} is allowed to be negative due to a BPV’s potential energy recuperation effect [Artmeier et al. [2010]]. Letting the vehicle’s charge capacity be B , we assume that $e_{ij} < B$ for all $(i, j) \in \mathcal{A}$. Since we are considering a single vehicle’s behavior, we assume that it will not affect the overall network’s traffic state, therefore, τ_{ij} and e_{ij} are assumed to be fixed depending on given traffic conditions at the time the single-vehicle routing problem is solved. Clearly, this cannot apply to the multi-vehicle case in the next section,

where the decisions of multiple vehicle routes affect traffic conditions, thus influencing traveling times and energy consumption. Since the BPV has limited battery energy it may not be able to reach the destination without recharging. Thus, recharging amounts at charging nodes $i \in \mathcal{N}$ are also decision variables.

We denote the selection of arc (i, j) and energy recharging amount at node i by $x_{ij} \in \{0, 1\}$, $i, j \in \mathcal{N}$ and $r_i \geq 0$, $i \in \mathcal{N}/\{n\}$, respectively. Moreover, since we take into account the vehicle’s energy constraints, we use E_i to represent the vehicle’s residual battery energy at node i . Then, for all E_j , $j \in O(i)$, we have:

$$E_j = \begin{cases} E_i + r_i - e_{ij} & \text{if } x_{ij} = 1 \\ 0 & \text{otherwise} \end{cases}$$

which can also be expressed as

$$E_j = \sum_{i \in I(j)} (E_i + r_i - e_{ij})x_{ij}, \quad x_{ij} \in \{0, 1\}$$

The problem objective is to determine a path from 1 to n , as well as recharging amounts, so as to minimize the total elapsed time for the vehicle to reach the destination. Fig. 1 is a sample network for this vehicle routing problem. We




Fig. 1. A 7-node network with charging nodes.

formulate an MINLP problem as follows:

$$\min_{x_{ij}, r_i, i, j \in \mathcal{N}} \sum_{i=1}^n \sum_{j=1}^n \tau_{ij} x_{ij} + \sum_{i=1}^n \sum_{j=1}^n r_i g x_{ij} \quad (1)$$

$$s.t. \quad \sum_{j \in O(i)} x_{ij} - \sum_{j \in I(i)} x_{ji} = b_i, \quad \text{for each } i \in \mathcal{N} \quad (2)$$

$$b_1 = 1, b_n = -1, b_i = 0, \text{ for } i \neq 1, n \quad (3)$$

$$E_j = \sum_{i \in I(j)} (E_i + r_i - e_{ij})x_{ij}, \text{ for } j = 2, \dots, n \quad (4)$$

$$0 \leq E_i \leq B, \quad E_1 \text{ given, for each } i \in \mathcal{N} \quad (5)$$

$$x_{ij} \in \{0, 1\}, \quad r_i \geq 0 \quad (6)$$

where g is the charging time per energy unit, i.e., the reciprocal of a fixed charging rate. The constraints (2)-(3) stand for the flow conservation, which implies that only one path starting from node i can be selected, i.e., $\sum_{j \in O(i)} x_{ij} \leq 1$. It is easy to check that this also implies $x_{ij} \leq 1$ for all i, j since $b_1 = 1$, $I(1) = \emptyset$. Constraint (4) represents the vehicle’s energy dynamics where the only non-linearity in this formulation appears. Finally, (5) indicates that the vehicle cannot run out of energy before reaching a node or exceed a given capacity B . All other parameters are predetermined according to the network topology.

2.1 Properties

Rather than directly tackling the MINLP problem, we derive some key properties which will enable us to simplify the solution procedure. The main difficulty in this problem

lies in the coupling of the decision variables, x_{ij} and r_i , in (4). The following lemma will enable us to exclude r_i from the objective function by showing that the difference between the total recharging energy and the total energy consumption while traveling is given only by the difference between the vehicle's residual energy at the destination and at the origin.

Lemma 1: Given (1)-(6),

$$\sum_{i=1}^n \sum_{j=1}^n (r_i x_{ij} - e_{ij} x_{ij}) = E_n - E_1 \quad (7)$$

Proof: See Wang et al. [2014]

In view of Lemma 1, we can replace $\sum_{i=1}^n \sum_{j=1}^n r_i g x_{ij}$ in (1) by $(E_n - E_1)g + \sum_{i=1}^n \sum_{j=1}^n e_{ij} g x_{ij}$ and eliminate the presence of r_i , $i = 2, \dots, n-1$, from the objective function. Note that E_1 is given, leaving us only with the task of determining the value of E_n . Now, let us investigate the recharging energy amounts r_i^* , $i = 1, \dots, n-1$, in an optimal policy. There are two possible cases: (i) $\sum_i r_i^* > 0$, i.e., the vehicle has to get recharged at least once, and (ii) $\sum_i r_i^* = 0$, i.e., $r_i^* = 0$ for all i and the vehicle has adequate energy to reach the destination without recharging. For Case (i), we establish the following lemma.

Lemma 2: If $\sum_i r_i^* > 0$ in the optimal routing policy, then $E_n^* = 0$.

Proof: See Wang et al. [2014]

Turning our attention to Case (ii) where $r_i^* = 0$ for all $i \in \{1, \dots, n\}$, observe that the problem (1) can be transformed to

$$\min_{x_{ij}, i, j \in \mathcal{N}} \sum_{i=1}^n \sum_{j=1}^n \tau_{ij} x_{ij} \quad (8)$$

$$s.t. \quad \sum_{j \in O(i)} x_{ij} - \sum_{j \in I(i)} x_{ji} = b_i, \quad \text{for each } i \in \mathcal{N}$$

$$b_1 = 1, b_n = -1, b_i = 0, \text{ for } i \neq 1, n$$

$$E_j = \sum_{i \in I(j)} (E_i - e_{ij}) x_{ij}, \text{ for } j = 2, \dots, n \quad (9)$$

$$0 \leq E_i \leq B, \quad E_0 \text{ given, for each } i \in \mathcal{N} \\ x_{ij} \in \{0, 1\} \quad (10)$$

In this case, the constraint (9) gives

$$\sum_{j=2}^n E_j - \sum_{j=2}^n \sum_{i \in I(j)} E_i = - \sum_{j=2}^n \sum_{i \in I(j)} e_{ij} x_{ij}$$

Recall that $E_i \geq 0$, we have

$$E_n = E_1 - \sum_{j=2}^n \sum_{i \in I(j)} e_{ij} x_{ij} \geq 0$$

and it follows that

$$\sum_{i=1}^n \sum_{j=1}^n e_{ij} x_{ij} \leq E_1 \quad (11)$$

With (11) in place of (9), the determination of x_{ij}^* boils down to an integer *linear* programming problem in which only variables x_{ij} , $i, j \in \mathcal{N}$, are involved, a much simpler problem.

We are normally interested in Case (i), where some recharging decisions must be made, so let us assume the

vehicle's initial energy is not large enough to reach the destination. Then, in view of Lemmas 1 and 2, we have the following theorem.

Theorem 1: If $\sum_i r_i^* > 0$ in the optimal policy, then x_{ij}^* , $i, j \in \mathcal{N}$, in the original problem (1) can be determined by solving a linear programming problem:

$$\min_{x_{ij}, i, j \in \mathcal{N}} \sum_{i=1}^n \sum_{j=1}^n (\tau_{ij} + e_{ij} g) x_{ij} \quad (12)$$

$$s.t. \quad \sum_{j \in O(i)} x_{ij} - \sum_{j \in I(i)} x_{ji} = b_i, \quad \text{for each } i \in \mathcal{N}$$

$$b_1 = 1, b_n = -1, b_i = 0, \text{ for } i \neq 1, n$$

$$0 \leq x_{ij} \leq 1$$

Proof: See Wang et al. [2014].

2.2 Determination of optimal recharging amounts r_i^*

Once we determine the optimal route, P , in (12), it is relatively easy to find a feasible solution for r_i , $i \in P$, to satisfy the constraint (4), which is obviously non-unique in general. Then, we can introduce a second objective into the problem, i.e., the minimization of charging costs on the selected path, since charging prices normally vary over stations. As before, we re-index nodes and define $P = \{1, \dots, n\}$. We denote the charging price at node i by p_i . Once an optimal route is determined, we seek to control the energy recharging amounts r_i to minimize the total charging cost dependent on p_i , $i \in \mathcal{N}/\{n\}$. This can be formulated as a multistage optimal control problem:

$$\min_{r_i, i \in P} \sum_{i \in P} p_i r_i \quad (13)$$

$$s.t. \quad E_{i+1} = E_i + r_i - e_{i,i+1}$$

$$0 \leq E_i \leq B, \quad E_1 \text{ given}$$

$$r_i \geq 0 \text{ for all } i \in \mathcal{N}$$

This is a simple two-point boundary-value problem and can be easily solved by discrete-time optimal control approaches [Bryson and Ho [1975]] or treating it as a linear programming problem where E_i and r_i are both decision variables. Due to space limitations, we omit numerical results providing example solutions of the simple linear programming problem (12) and subsequent solutions of (13). Finally, we note that Theorem 1 holds under the assumption that charging nodes are homogeneous in terms of charging speeds (i.e., the charging rate $1/g$ is fixed). However, our analysis allows for inhomogeneous charging prices. The case of node-dependent charging rates is the subject of ongoing work and can be shown to still allow a decomposition of the MINLP, although we can no longer generally obtain an LP.

3. MULTIPLE VEHICLE ROUTING

The results obtained for the single vehicle routing problem pave the way for the investigation of multi-vehicle routing, where we seek to optimize a system-wide objective by routing vehicles through the same network topology. The main technical difficulty in this case is that we need to consider the influence of traffic congestion on both traveling time and energy consumption. A second difficulty is that of implementing an optimal routing policy. In the

case of a centrally controlled system consisting of mobile robots, sensors or any type of autonomous vehicles this can be accomplished through appropriately communicated commands. In the case of vehicles with individual drivers, implementation requires signaling mechanisms and possibly incentive structures to enforce desired routes assigned to vehicles, bringing up a number of additional research issues. In the sequel, we limit ourselves to resolving the first difficulty before addressing implementation challenges.

If we proceed as in the single vehicle case, i.e., determining a path selection through x_{ij}^k , $i, j \in \mathcal{N}$, and recharging amounts r_i^k , $i \in \mathcal{N}/\{n\}$ for all vehicles $k = 1, \dots, K$, for some K , then the dimensionality of the solution space is prohibitive. Moreover, the inclusion of traffic congestion effects introduces additional nonlinearities in the dependence of the travel time τ_{ij} and energy consumption e_{ij} on the traffic flow through arc (i, j) , which now depend on $x_{ij}^1, \dots, x_{ij}^K$. Instead, we will proceed by grouping subsets of vehicles into N "subflows" where N may be selected to render the problem manageable.

Let all vehicles enter the network at the origin node 1 and let R denote the rate of vehicles arriving at this node. Viewing vehicles as defining a *flow*, we divide them into N *subflows* (we will discuss the effect of N in Section 3.3), each of which may be selected so as to include the same type of homogeneous vehicles (e.g., large vehicles vs smaller ones or vehicles with the same initial energy). Thus, all vehicles in the same subflow follow the same routing and recharging decisions so that we only consider energy recharging at the subflow level rather than individual vehicles. Note that asymptotically, as $N \rightarrow \infty$, we can recover routing at the individual vehicle level.

Clearly, not all vehicles in our system are BPVs and are, therefore, not part of our optimization process. These can be treated as uncontrollable interfering traffic for our purposes and can be readily accommodated in our analysis, as long as their flow rates are known. However, for simplicity, we will assume here that every arriving vehicle is a BPV and joins a subflow.

Our objective is to determine optimal routes and energy recharging amounts for each subflow of vehicles so as to minimize the total elapsed time of these vehicle flows traveling from the origin to the destination. The decision variables consist of $x_{ij}^k \in \{0, 1\}$ for all arcs (i, j) and subflows $k = 1, \dots, N$, as well as charging amounts r_i^k for all nodes $i = 1, \dots, n-1$ and $k = 1, \dots, N$. Given traffic congestion effects, the time and energy consumption on each arc depends on the values of x_{ij}^k and the fraction of the total flow rate R associated with each subflow k ; the simplest such flow allocation is one where each subflow is assigned R/N . Let $\mathbf{x}_{ij} = (x_{ij}^1, \dots, x_{ij}^N)^T$ and $\mathbf{r}_i = (r_i^1, \dots, r_i^N)^T$. Then, we denote the traveling time and corresponding energy consumption of the k th vehicle subflow on arc (i, j) by $\tau_{ij}^k(\mathbf{x}_{ij})$ and $e_{ij}^k(\mathbf{x}_{ij})$ respectively. As already mentioned, $\tau_{ij}^k(\mathbf{x}_{ij})$ and $e_{ij}^k(\mathbf{x}_{ij})$ can also incorporate the influence of uncontrollable (non-BPV) vehicle flows, which can be treated as parameters in these functions. Similar to the single vehicle case, we use E_i^k to represent the residual energy of subflow k at node i , given by the aggregated residual energy of all vehicles in the

subflow. If the subflow does not go through node i , then $E_i^k = 0$. The problem formulation is as follows:

$$\min_{\mathbf{x}_{ij}, \mathbf{r}_i, i, j \in \mathcal{N}} \sum_{i=1}^n \sum_{j=1}^n \sum_{k=1}^N (\tau_{ij}^k(\mathbf{x}_{ij}) + r_i^k g x_{ij}^k) \quad (14)$$

s.t. for each $k \in \{1, \dots, N\}$:

$$\sum_{j \in O(i)} x_{ij}^k - \sum_{j \in I(i)} x_{ji}^k = b_i, \quad \text{for each } i \in \mathcal{N} \quad (15)$$

$$b_1 = 1, b_n = -1, b_i = 0, \quad \text{for } i \neq 1, n \quad (16)$$

$$E_j^k = \sum_{i \in I(j)} (E_i^k + r_i^k - e_{ij}^k(\mathbf{x}_{ij})) x_{ij}^k, \quad j = 2, \dots, n \quad (17)$$

$$E_1^k \text{ is given, } E_i^k \geq 0, \quad \text{for each } i \in \mathcal{N} \quad (18)$$

$$x_{ij}^k \in \{0, 1\}, \quad r_i^k \geq 0 \quad (19)$$

Obviously, this MINLP problem is difficult to solve. However, as in the single-vehicle case, we are able to establish some properties that will allow us to simplify it.

3.1 Properties

Even though the term $\tau_{ij}^k(\mathbf{x}_{ij})$ in the objective function is no longer linear in general, for each subflow k the constraints (15)-(19) are still similar to the single-vehicle case. Consequently, we can derive similar useful properties for this problem in the form of the following two lemmas.

Lemma 3: For each subflow $k = 1, \dots, N$,

$$\sum_{i=1}^n \sum_{j=1}^n (r_i^k - e_{ij}^k(\mathbf{x}_{ij})) x_{ij}^k = E_n^k - E_1^k \quad (20)$$

Lemma 4: If $\sum_{i=1}^n r_i^{k*} > 0$ in the optimal routing policy, then $E_n^{k*} = 0$ for all $k = 1, \dots, N$.

Proof: See Wang et al. [2014].

In view of Lemma 3, we can replace $\sum_{i=1}^n \sum_{j=1}^n r_i^k g x_{ij}^k$ in (14) by $(E_n^k - E_1^k)g + \sum_{i=1}^n \sum_{j=1}^n e_{ij}^k(\mathbf{x}_{ij}) g x_{ij}^k$ and eliminate, for all $k = 1, \dots, N$, the presence of r_i^k , $i = 1, \dots, n-1$, from the objective function similar to the single-vehicle case. Since E_1^k is given, this leaves only the task of determining the value of E_n^k . There are two possible cases: (i) $\sum_i r_i^{k*} > 0$, i.e., the k th vehicle subflow has to get recharged at least once, and (ii) $\sum_i r_i^{k*} = 0$, i.e., $r_i^{k*} = 0$ for all i and the k th vehicle subflow has adequate energy to reach the destination without recharging.

Similar to the derivation of (11), Case (ii) results in a new constraint $\sum_i \sum_j e_{ij}^k(\mathbf{x}_{ij}) x_{ij}^k \leq E_1^k$ for subflow k . However, since $e_{ij}^k(\mathbf{x}_{ij})$ now depends on all $x_{ij}^1, \dots, x_{ij}^N$, the problem (14)-(19) with all $r_i^k = 0$ is not as simple to solve as was the case with (8)-(10). Let us instead concentrate on the more interesting Case (i) for which Lemma 4 applies and we have $E_n^{k*} = 0$. Therefore, along with Lemma 3, we have for each $k = 1, \dots, N$:

$$\sum_{i=1}^n \sum_{j=1}^n r_i^k x_{ij}^k = \sum_{i=1}^n \sum_{j=1}^n e_{ij}^k(\mathbf{x}_{ij}) x_{ij}^k - E_1^k$$

Then, proceeding as in Theorem 1, we can replace the original objective function (14) and have the following new problem formulation to determine x_{ij}^{k*} for all $i, j \in \mathcal{N}$ and $k = 1, \dots, N$:

$$\begin{aligned} \min_{\mathbf{x}_{ij}, i, j \in \mathcal{N}} \quad & \sum_{i=1}^n \sum_{j=1}^n \sum_{k=1}^N (\tau_{ij}^k(\mathbf{x}_{ij}) + e_{ij}^k(\mathbf{x}_{ij})g x_{ij}^k) \quad (21) \\ \text{s.t.} \quad & \sum_{j \in O(i)} x_{ij}^k - \sum_{j \in I(i)} x_{ji}^k = b_i, \quad \text{for each } i \in \mathcal{N} \\ & b_1 = 1, b_n = -1, b_i = 0, \text{ for } i \neq 1, n \\ & x_{ij}^k \in \{0, 1\} \end{aligned}$$

Since the objective function is no longer necessarily linear in x_{ij}^k , (21) cannot be further simplified into an LP problem as in Theorem 1. The computational effort required to solve this problem heavily depends on the dimensionality of the network and the number of subflows. Nonetheless, from the transformed formulation above, we are still able to separate the determination of routing variables x_{ij}^k from recharging amounts r_i^k . Similar to the single-vehicle case, once the routes are determined, we can obtain any r_i^k satisfying the energy constraints (17)-(18) such that $E_n^k = 0$, thus preserving the optimality of the objective value. To further determine r_i^{k*} , we can introduce a second level optimization problem similar to the single-vehicle case in (13). Next, we will present an alternative formulation for the original problem (14)-(19) which leads to a computationally simpler solution approach.

3.2 Flow control formulation

We begin by relaxing the binary variables in (19) by letting $0 \leq x_{ij}^k \leq 1$. Thus, we switch our attention from determining a single path for any subflow k to several possible paths by treating x_{ij}^k as the normalized vehicle flow on arc (i, j) for the k th subflow. This is in line with many network routing algorithms in which fractions x_{ij} of entities are routed from a node i to a neighboring node j using appropriate schemes ensuring that, in the long term, the fraction of entities routed on (i, j) is indeed x_{ij} . Following this relaxation, the objective function in (14) is changed to:

$$\min_{\mathbf{x}_{ij}, \mathbf{r}_i, i, j \in \mathcal{N}} \quad \sum_{i=1}^n \sum_{j=1}^n \sum_{k=1}^N \tau_{ij}^k(\mathbf{x}_{ij}) + \sum_{i=1}^n \sum_{k=1}^N r_i^k g$$

Moreover, the energy constraint (17) needs to be adjusted accordingly. Let E_{ij}^k represent the fraction of residual energy of subflow k associated with the x_{ij}^k portion of the vehicle flow exiting node i . Therefore, the constraint (18) becomes $E_{ij}^k \geq 0$. We can now capture the relationship between the energy associated with subflow k and the vehicle flow as follows:

$$\left[\sum_{h \in I(i)} (E_{hi}^k - e_{hi}^k(\mathbf{x}_{ij})) + r_i^k \right] \cdot \frac{x_{ij}^k}{\sum_{h \in I(i)} x_{hi}^k} = E_{ij}^k \quad (22)$$

$$\frac{E_{ij}^k}{\sum_{j \in O(i)} E_{ij}^k} = \frac{x_{ij}^k}{\sum_{j \in O(i)} x_{ij}^k} \quad (23)$$

In (22), the energy values of different vehicle flows entering node i are aggregated and the energy corresponding to each portion exiting a node, E_{ij}^k , $j \in O(i)$, is proportional to the corresponding fraction of vehicle flows, as expressed in (23). Clearly, this aggregation of energy leads to an approximation, since one specific vehicle flow may need to be recharged in order to reach the next node in its

path, whereas another might have enough energy without being recharged. This approximation foregoes controlling recharging amounts at the individual vehicle level and leads to approximate solutions of the original problem (14)-(19). Several numerically based comparisons are provided in the next section and Wang et al. [2014] showing little or no loss of optimality relative to the solution of (14).

Adopting this formulation with $x_{ij}^k \in [0, 1]$ instead of $x_{ij}^k \in \{0, 1\}$, we obtain the following simpler nonlinear programming problem (NLP):

$$\min_{\mathbf{x}_{ij}, \mathbf{r}_i, i, j \in \mathcal{N}} \quad \sum_{i=1}^n \sum_{j=1}^n \sum_{k=1}^N \tau_{ij}^k(\mathbf{x}_{ij}) + \sum_{i=1}^n \sum_{k=1}^N r_i^k g \quad (24)$$

$$\text{s.t.} \quad \sum_{j \in O(i)} x_{ij}^k - \sum_{j \in I(i)} x_{ji}^k = b_i, \quad \text{for each } i \in \mathcal{N} \quad (25)$$

$$b_1 = 1, b_n = -1, b_i = 0, \text{ for } i \neq 1, n$$

$$\left[\sum_{h \in I(i)} (E_{hi}^k - e_{hi}^k(\mathbf{x}_{ij})) + r_i^k \right] \cdot \frac{x_{ij}^k}{\sum_{h \in I(i)} x_{hi}^k} = E_{ij}^k \quad (26)$$

$$\frac{E_{ij}^k}{\sum_{j \in O(i)} E_{ij}^k} = \frac{x_{ij}^k}{\sum_{j \in O(i)} x_{ij}^k} \quad (27)$$

$$E_{ij}^k \geq 0, \quad (28)$$

$$0 \leq x_{ij}^k \leq 1, \quad r_i^k \geq 0 \quad (29)$$

As in our previous analysis, we are able to eliminate \mathbf{r}_i from the objective function in (24) as follows.

Lemma 5: For each subflow $k = 1, \dots, N$,

$$\sum_{i=1}^n r_i^k = \sum_{i=1}^n \sum_{j=1}^n e_{ij}^k(\mathbf{x}_{ij}) + \sum_{i \in I(n)} E_{in}^k - \sum_{i \in O(1)} E_{1i}^k$$

Proof: See Wang et al. [2014]

Similar to Lemma 3, we can easily see that if $\sum_i r_i^{k*} > 0$ under an optimal routing policy, then $\sum_{i \in I(n)} E_{in}^{k*} = 0$. In addition, $\sum_{i \in O(1)} E_{1i}^k = E_1^k$, which is given. We can now transform the objective function (24) into (30) and determine the optimal routes x_{ij}^{k*} by solving the following NLP:

$$\min_{\mathbf{x}_{ij}, i, j \in \mathcal{N}} \quad \sum_{k=1}^N \left(\sum_{i=1}^n \sum_{j=1}^n [\tau_{ij}^k(\mathbf{x}_{ij}) + e_{ij}^k(\mathbf{x}_{ij})g] - E_1^k \right) \quad (30)$$

$$\text{s.t.} \quad \sum_{j \in O(i)} x_{ij}^k - \sum_{j \in I(i)} x_{ji}^k = b_i, \quad \text{for each } i \in \mathcal{N}$$

$$b_1 = 1, b_n = -1, b_i = 0, \text{ for } i \neq 1, n$$

$$0 \leq x_{ij}^k \leq 1$$

The values of r_i^k , $i = 1, \dots, n$, $k = 1, \dots, N$, can be determined so as to satisfy the energy constraints (26)-(28), and they are obviously not unique. We may then proceed with a second-level optimization problem to determine optimal values similar to Section 2.2.

3.3 Numerical Examples

Using the relationship between speed and density of a vehicle flow introduced in Ho and Ioannou [1996], the time subflow k spends on arc (i, j) becomes:

$$\tau_{ij}^k(\mathbf{x}_{ij}) = \frac{d_{ij} \cdot x_{ij}^k \cdot \frac{R}{N}}{v_f(1 - (\sum_k x_{ij}^k)^p)^q}$$

where v_f is the reference speed on the road without traffic and the parameters p and q are empirically identified for actual traffic flows (for more details see Wang et al. [2014].) Note that we do not include uncontrollable vehicle flows in our example for simplicity. As for $e_{ij}^k(\mathbf{x}_{ij})$, we assume the energy consumption rates of subflows on arc (i, j) are all identical, proportional to the distance between nodes i and j , giving $e_{ij}^k(\mathbf{x}_{ij}) = e \cdot d_{ij} \cdot R/N$. Therefore, we aim to solve the multi-vehicle routing problem (21) with the objective function as follows in this case:

$$\min_{x_{ij}^k} \sum_{i=1}^n \sum_{j=1}^n \sum_{k=1}^N \left(\frac{d_{ij} x_{ij}^k \frac{R}{N}}{v_f(1 - (\sum_k x_{ij}^k)^p)^q} + e g d_{ij} \frac{R}{N} x_{ij}^k \right) \quad (31)$$

For simplicity, we let $v_f = 1$ mile/min, $R = 1$ vehicle/min, $p = 2$, $q = 2$ and $e \cdot g = 1$. The network topology used is that of Fig.1, where the distance of each arc is as shown. The results of solving this problem are shown in Tab. 1 for different values of N . It can be seen that the traffic congestion effect makes the flow distribution differ from following the shortest path. The number of decision variables (hence, the solution search space) rapidly increases with the number of subflows. However, it is observed that the optimal objective value quickly converges around $N = 10$. Thus, even though the best solution is found when $N = 25$, a near-optimal solution can be determined under a small number of subflows. This suggests that one can rapidly approximate the asymptotic solution of the multi-vehicle problem (dealing with individual vehicles routed so as to optimize a systemwide objective) based on a relatively small value of N . Next, we obtain a solution to the same

Table 1. Numerical results for sample problem

N	2	10
obj	37.077	31.5279
routes	1 → 4 → 7 1 → 2 → 3 → 7	(1 → 4 → 7) × 4 (1 → 2 → 3 → 7) × 3 (1 → 5 → 6 → 7) × 3
N	15	30
obj	31.4851	31.4768
routes	(1 → 4 → 7) × 5 (1 → 2 → 3 → 7) × 5 (1 → 5 → 6 → 7) × 4 (1 → 4 → 6 → 7) × 1	(1 → 4 → 7) × 11 (1 → 2 → 3 → 7) × 10 (1 → 5 → 6 → 7) × 8 (1 → 4 → 6 → 7) × 1

problem (31) using the alternative NLP formulation (30) where $0 \leq x_{ij}^k \leq 1$. Since in this example all subflows are identical, we can further combine all x_{ij}^k over each arc (i, j) , which leads to the N -subflow relaxed problem (refer to Wang et al. [2014]). Using the same parameter settings as before, we obtain the objective value of 31.4465 mins and the optimal routes are: 35.88% of vehicle flow: (1 → 4 → 7); 31.74% of vehicle flow: (1 → 2 → 3 → 7); 27.98% of vehicle flow: (1 → 5 → 6 → 7); 4.44% of vehicle flow: (1 → 4 → 6 → 7). Note that, the difference in objective values between the integer and flow-based solutions is less than 0.1%. This supports the effectiveness of a solution based on a limited number of subflows in the

MINLP problem. Additional numerical examples may be found in Wang et al. [2014].

4. CONCLUSIONS AND FUTURE WORK

We have introduced energy constraints into the vehicle routing problem, and studied the problem of minimizing the total elapsed time for vehicles to reach their destinations by determining routes as well as recharging amounts when there is no adequate energy for the entire journey. For a single vehicle, we have shown how to decompose this problem into two simpler problems. For a multi-vehicle problem, where traffic congestion effects are considered, we used a similar approach by aggregating vehicles into subflows and seeking optimal routing decisions for each subflow. We also developed an alternative flow-based formulation which yields approximate solutions with a computational cost reduction of several orders of magnitude, suitable for large problems. Numerical examples show these solutions to be near-optimal.

Our ongoing work introduces different characteristics into the charging stations, such as recharging speeds and queuing capacities. We also believe that extensions to multiple vehicle origins and destinations are straight-forward, as is the case where only a subset of nodes has recharging resources or not all vehicles in the network are BPVs.

REFERENCES

- Artmeier, A., Haselmayr, J., Leucker, M., and Sachenbacher, M. (2010). The optimal routing problem in the context of battery-powered electric vehicles. In *2nd Intl. W/shop on Constraint Reasoning and Optim. for Comput. Sustainability*.
- Bertsimas, D. and Tsitsiklis, J.N. (1997). *Introduction to Linear Programming*. Athena Scientific.
- Bryson, A.E. and Ho, Y. (1975). *Applied Optimal Control*. Hemisphere Publ. Corp.
- Eisner, J., Funke, S., and Storandt, S. (2011). Optimal route planning for electric vehicles in large networks. In *Proc. of the 25th AAAI Conf. on Artif. Intelligence*.
- Ho, F. and Ioannou, P. (1996). Traffic flow modeling and control using artificial neural networks. *Control Systems, IEEE*, 16, 16 – 26.
- Khuller, S., Malekian, A., and Mestre, J. (2011). To fill or not to fill: The gas station problem. *ACM Transactions on Algorithms*, 7.
- Laporte, G. (1992). The vehicle routing problem: An overview of exact and approximate algorithms. *European Journal of Operational Research*, 59.
- Schneider, M., Stenger, A., and Goeke, D. (2012). The electric vehicle routing problem with time windows and recharging stations. Tech Report, Dept. of Business Info. Systems and Oper. Res., U. of Kaiserslautern.
- Siddiqi, U.F., Shirraishi, Y., and Sait, S.M. (2011). Multi-constrained route optimization for electric vehicles (evs) using particle swarm optimization. In *2011 11th Intl. Conf. on Intell. Systems Design and Applic.*, 391–396.
- Sunder, K. and Rathinam, S. (2012). Route planning algorithms for unmanned aerial vehicles with refueling constraints. In *2012 ACC*, 3266–3271.
- Wang, R., Cassandras, C., and Pourazarm, S. (2014). Energy-aware vehicle routing in networks with charging stations. In *arXiv:1401.6478*.